



For Sale
On Lease

INFORMATION



- Available Sizes - **10Ft / 20Ft / 40Ft**
- **Compact, Portable and Robust structure**
- Complete **Stainless Steel Interior**
- **Power Efficient & High Durability**
- **Customizable** as per the requirement
- **T-Bar** as well as **Plain Floor**
- Load Carrying capacity: **10Ft-8Ton | 20Ft-25Ton | 40Ft-30Ton**
- Temperature - **Plus 25 Deg C to Minus 30 Deg C**
- **Reliable Refrigeration System.**
- Next-Generation "**CrystalSMART**" **Remote Monitoring**
- **External Ramp** for Loading & Unloading
- **LED Light** inside the Container for Visibility
- **Man Trap Alarm** for safety purpose
- **Strip Curtains** to avoid Heat Loss
- **Microprocessor Based Controller**
- **1 Working + 1 Standby** for business continuity
- **Anti Room** for Pre-cooling & Avoid Heat Loss
- Suitable to store **Pharma, Dairy, Fruit, Chemical, Food, Medicine, Vegetable products, R&D, Construction, Engineering etc**



Contact us:

9892512900 / 9136121497

marketing@crystalgroup.in www.crystalgroup.in



PAN INDIA PRESENCE



FOOD SAFETY CERTIFIED





FOR LEASE & SALE

REEFER CONTAINER SPECIFICATION

| Container Model | 10 FEET | | 20 FEET | | 40 FEET | |
|------------------------|---|----------|----------------|----------|----------------|----------|
| Dimensions | EXTERNAL | INTERNAL | EXTERNAL | INTERNAL | EXTERNAL | INTERNAL |
| Length [mm] | 2990 | 2265 | 6060 | 5340 | 12180 | 11500 |
| Width [mm] | 2440 | 2290 | 2440 | 2290 | 2440 | 2290 |
| Height [mm] | 2580 | 2270 | 2580 | 2270 | 2890 | 2600 |
| Max Gross | 10160 KGS | | 30480 KGS | | 34000 KGS | |
| TARE | 2020 KGS | | 3040 KGS | | 4720 KGS | |
| NET | 8140 KGS | | 27440 KGS | | 29280 KGS | |
| Cubic Cap | 12.4 CUBIC MTR | | 28.2 CUBIC MTR | | 67.9 CUBIC MTR | |
| CLADDING | EXTERNAL | INTERNAL | EXTERNAL | INTERNAL | EXTERNAL | INTERNAL |
| SIDE | MGSS | HGSS | MGSS | HGSS | MGSS | HGSS |
| ROOF | MGSS | PP | MGSS | PP | MGSS | PP |
| BASE | MGSS | AL | MGSS | AL | MGSS | AL |
| DOOR | MGSS | AL | MGSS | AL | MGSS | AL |
| REF GAS | R-134A R-404A - CFC FREE [ECO-FRIENDLY] | | | | | |
| POWER | 440V-3PH-50Hz | | | | | |
| NOISE | LESS THAN 70 dB | | | | | |